INDEX

Author/Title Index

Asakawa, Y.: See Kiyono, S., 68

Basile, S. A.
Modeling transverse motions of a drill bit for process understanding, 258
Battles, A. E., Linder, B. M., Chang, K. W., and Slocum, A. H.
The design of a precision bilaminar resonating transducer assembly tool, 248
Bifano, T. G., DePiero, D. K., and Golini, D.
Chemomechanical effects in ductile-regime machining of glass, 238
Bittner, B.: See Wäldele, F., 121
Blaedel, K. L.: Comment, 4
Bobroff, N.
Critical alignments in plane mirror interferometry, 33
Borchardt, B.: See Phillips, S. D., 16
Bourdet, P., Lartigue, C., and Leveaux, F.
Effects of data point distribution and mathematical model on finding the best-fit sphere to data, 150
Busch, K.: See Wäldele, F., 121

Carr, J. W., and Feger, C.
Ultraprecision machining of polymers, 221
Chang, K. W.: See Battles, A. E., 248
Chong, A. K. F., and Lieu, D. K.
Contour mapping of precision ball defects with laser Doppler vibrometry, 166

DePiero, D. K.: See Bifano, T. G., 238
Doiron, T.: See Phillips, S. D., 16
Downs, M. J., and Rowley, W. R. C.
A proposed design for a polarization-insensitive optical interferometer system with subnanometric capability, 281
Drescher, J.
Scanning electron microscopic technique for imaging a diamond tool edge, 112
Drieschner, R.: See Wäldele, F., 121

Elligsen, R.: See Wäldele, F., 121

Fan, K. C.: See Huang, S. T., 25, 158
Feger, C.: See Carr, J. W., 221

Gao, R. X.: See Warrington, R. O., 193
Golini D.: See Bifano, T. G., 238
Goto, M.: See Nakamura, O., 39

Hatamura, Y., Nagao, T., and Mitsuishi, M.
A fundamental structure for intelligent manufacturing, 266
Henry, J.: See Phillips, S. D., 16
Hetrick, P. S.: See Oldham, N. M., 173
Hong, S. Y.
On material selection for ultra-high accuracy and high-speed machine table for applications such as E-beam lithography, 115
Huang, S. T., Fan, K. C., and Wu, J. H.
A new minimum zone method for evaluating flatness errors, 25
Huang, S. T., Fan, K. C., and Wu, J. H.
A new minimum zone method for evaluating straightness errors, 158

Inamoto, M.: See Kiyono, S., 68

Jain, V. K.: See Koshy, P., 6

Kamada, O.: See Kiyono, S., 68
Kamiya, K.: See Nomura, T., 86
Kanada, T., and Suzuki, S.
Application of several computing techniques for minimum zone straightness, 274
Kanada, T., and Suzuki, S.
Evaluation of minimum zone flatness by means of nonlinear optimization techniques and its verification, 93
Kiyono, S., Asakawa, Y., Inamoto, M., and Kamada, O.
A differential laser autocollimation probe for on-machine measurement, 68
Kobayashi, F.: See Nomura, T., 86
Koshy, P., Jain, V. K., and Lal, G. K.
Experimental investigations into electrical discharge machining with a rotating disk electrode, 6
Kramar, J. A.: See Oldham, N. M., 173
Kyusojin, A.: See Oiwa, T., 106

Lal, G. K.: See Koshy, P., 6
Lartigue, C.: See Bourdet, P., 150
Leveaux, F.: See Bourdet, P., 150
Lieu, D. K.: See Chong, A. K. F., 166
Linder, B. M.: See Battles, A. E., 248
Loh, N. H., Tam, S. C., and Miyazawa, S.
Ball burnishing of tool steel, 100

Mainsah, E., and Stout, K. J.
Second international workshop on the development of methods for the characterization of roughness in 3-D, 287
Matsubara, T.: See Mizumoto, H., 180
Mattsson, L., and Wågberg, P.
Assessment of surface finish on bulk scattering materials: a comparison between optical laser stylus and mechanical stylus profilometers, 141
Mitsuishi, M.: See Hatamura, Y., 266
Miyashiro, H.: See Nomura, T., 86
Miyazawa, S.: See Loh, N. H., 100
Mizumoto, H., Nomura, K., Matsubara, T., and Shimizu, T.
An ultraprecision positioning system using a twist-roller friction drive, 180

Nagao, T.: See Hatamura, Y., 266
Nakamura, O., and Goto, M.
Laser interferometric calibration of microscan mechanisms by using three laser beams, 39
Nomura, K.: See Mizumoto, H., 180
Nomura, T., Miyashiro, H., Kamiya, K., Yoshikawa, K., Tashiro, H., Suzuki, M., Usuki, M., and Kobayashi, F.
Shape measurement of workpiece surface with zone-plate interferometer during machine running, 86

Oiwa, T., and Kyusojin, A.
Development of precise cylindrical grinding by ball centers: effect of ball wear, 106
Oldham, N. M., Kramar, J. A., Hetrick, P. S., and Teague, E. C.
Electronic limitations in phase meters for heterodyne interferometry, 173

Phillips, S. D., Borchardt, B., Doiron, T., and Henry, J.
Properties of free-standing ball bar systems, 16

Rowley, W. R. C.: See Downs, M. J., 281

INDEX

Author/Title Index

Asakawa, Y.: See Kiyono, S., 68

Basile, S. A.
Modeling transverse motions of a drill bit for process understanding, 258
Battles, A. E., Linder, B. M., Chang, K. W., and Slocum, A. H.
The design of a precision bilaminar resonating transducer assembly tool, 248
Bifano, T. G., DePiero, D. K., and Golini, D.
Chemomechanical effects in ductile-regime machining of glass, 238
Bittner, B.: See Wäldele, F., 121
Blaedel, K. L.: Comment, 4
Bobroff, N.
Critical alignments in plane mirror interferometry, 33
Borchardt, B.: See Phillips, S. D., 16
Bourdet, P., Lartigue, C., and Leveaux, F.
Effects of data point distribution and mathematical model on finding the best-fit sphere to data, 150
Busch, K.: See Wäldele, F., 121

Carr, J. W., and Feger, C.
Ultraprecision machining of polymers, 221
Chang, K. W.: See Battles, A. E., 248
Chong, A. K. F., and Lieu, D. K.
Contour mapping of precision ball defects with laser Doppler vibrometry, 166

DePiero, D. K.: See Bifano, T. G., 238
Doiron, T.: See Phillips, S. D., 16
Downs, M. J., and Rowley, W. R. C.
A proposed design for a polarization-insensitive optical interferometer system with subnanometric capability, 281
Drescher, J.
Scanning electron microscopic technique for imaging a diamond tool edge, 112
Drieschner, R.: See Wäldele, F., 121

Elligsen, R.: See Wäldele, F., 121

Fan, K. C.: See Huang, S. T., 25, 158
Feger, C.: See Carr, J. W., 221

Gao, R. X.: See Warrington, R. O., 193
Golini D.: See Bifano, T. G., 238
Goto, M.: See Nakamura, O., 39

Hatamura, Y., Nagao, T., and Mitsuishi, M.
A fundamental structure for intelligent manufacturing, 266
Henry, J.: See Phillips, S. D., 16
Hetrick, P. S.: See Oldham, N. M., 173
Hong, S. Y.
On material selection for ultra-high accuracy and high-speed machine table for applications such as E-beam lithography, 115
Huang, S. T., Fan, K. C., and Wu, J. H.
A new minimum zone method for evaluating flatness errors, 25
Huang, S. T., Fan, K. C., and Wu, J. H.
A new minimum zone method for evaluating straightness errors, 158

Inamoto, M.: See Kiyono, S., 68

Jain, V. K.: See Koshy, P., 6

Kamada, O.: See Kiyono, S., 68
Kamiya, K.: See Nomura, T., 86
Kanada, T., and Suzuki, S.
Application of several computing techniques for minimum zone straightness, 274
Kanada, T., and Suzuki, S.
Evaluation of minimum zone flatness by means of nonlinear optimization techniques and its verification, 93
Kiyono, S., Asakawa, Y., Inamoto, M., and Kamada, O.
A differential laser autocollimation probe for on-machine measurement, 68
Kobayashi, F.: See Nomura, T., 86
Koshy, P., Jain, V. K., and Lal, G. K.
Experimental investigations into electrical discharge machining with a rotating disk electrode, 6
Kramar, J. A.: See Oldham, N. M., 173
Kyusojin, A.: See Oiwa, T., 106

Lal, G. K.: See Koshy, P., 6
Lartigue, C.: See Bourdet, P., 150
Leveaux, F.: See Bourdet, P., 150
Lieu, D. K.: See Chong, A. K. F., 166
Linder, B. M.: See Battles, A. E., 248
Loh, N. H., Tam, S. C., and Miyazawa, S.
Ball burnishing of tool steel, 100

Mainsah, E., and Stout, K. J.
Second international workshop on the development of methods for the characterization of roughness in 3-D, 287
Matsubara, T.: See Mizumoto, H., 180
Mattsson, L., and Wågberg, P.
Assessment of surface finish on bulk scattering materials: a comparison between optical laser stylus and mechanical stylus profilometers, 141
Mitsuishi, M.: See Hatamura, Y., 266
Miyashiro, H.: See Nomura, T., 86
Miyazawa, S.: See Loh, N. H., 100
Mizumoto, H., Nomura, K., Matsubara, T., and Shimizu, T.
An ultraprecision positioning system using a twist-roller friction drive, 180

Nagao, T.: See Hatamura, Y., 266
Nakamura, O., and Goto, M.
Laser interferometric calibration of microscan mechanisms by using three laser beams, 39
Nomura, K.: See Mizumoto, H., 180
Nomura, T., Miyashiro, H., Kamiya, K., Yoshikawa, K., Tashiro, H., Suzuki, M., Usuki, M., and Kobayashi, F.
Shape measurement of workpiece surface with zone-plate interferometer during machine running, 86

Oiwa, T., and Kyusojin, A.
Development of precise cylindrical grinding by ball centers: effect of ball wear, 106
Oldham, N. M., Kramar, J. A., Hetrick, P. S., and Teague, E. C.
Electronic limitations in phase meters for heterodyne interferometry, 173

Phillips, S. D., Borchardt, B., Doiron, T., and Henry, J.
Properties of free-standing ball bar systems, 16

Rowley, W. R. C.: See Downs, M. J., 281

Sherrington, I., and Smith, E. H. Design and performance assessment of a Kelvin clamp for use in relocation analysis of surface topography, 77
Shimizu, T.: See Mizumoto, H., 180
Slocum, A. H.: See Battles, A. E., 248
Smith, E. H.: See Sherrington, I., 77
Soons, H. A.: Letter to Editor, 44
Stout, K. J.: See Mainsah, E., 287
Suzuki, M.: See Nomura, T., 86
Suzuki, S.: See Kanada, T., 93, 274

Tam, S. C.: See Loh, N. H., 100
Tashiro, H.: See Nomura, T., 86
Teague, E. C.: See Oldham, N. M., 173

Usuki, M.: See Nomura, T., 86

Wågberg, P.: See Mattsson, L., 141
Wäldele, F., Bittner, B., Busch, K., Drieschner, R., and Elligsen, R. Testing of coordinate measuring machine software, 121
Warrington, R. O., and Gao, R. X. Institute for Micromanufacturing: A Louisiana Initiative in MEMS, 193
Wu, J. H.: See Huang, S. T., 25, 158

Yoshikawa, K.: See Nomura, T., 86

Keyword Index

Actuator, 266

Ball burnishing, 100
Ball center, 106
Ball wear, 106
Ball, 166
Bilaminar, 248
Brittle materials, 238

Calibration, 39
Chemomechanical effects, 238
Contact pressure, 106
Contour, 166
Convergence criteria, 93, 274
Coordinate measuring machine, 16, 121, 150
Coordinate measurement, 33
Crack, 166
Cylindrical grinding, 106

Defect, 166
Diamond tool edge, 112
Differential laser autocollimation, 68
Downhill simplex method, 93
Drill transverse motion model, 258

E-beam lithography, 115
Electrical discharge machining, 6

Flatness, 25, 274
Flexures, 248
Free-standing ball bar, 16
Friction drive, 180
Frictional torque, 106

Grinding, 238

Heterodyne interferometry, 173
Hole roundness, 258
Hydrostatic bearing, 180

Information, 266
Intelligent manufacturing, 266
Interferometers, 33

Kelvin clamp, 77
Kinematic, 248

Laser interferometry, 39
Laser, 166
Lead screw, 180
Least-squares method, 25, 93, 158, 274
Least squares, 39
Linear search, 274
Linearization, 274
Lubrication, 106

Machining center, 266
Machining condition, 93
Mapping, 166
Material selection, 115
Measurement systems, 141
Measurement during workpiece turning, 86
Mechanical stylus, 141
Metrology, 33
Microscanning mechanism, 39
Minimum zone flatness, 93
Minimum zone method, 25, 158, 274

On-machine measurement, 68, 86
Optical fabrication, 238
Optical interferometer system, 281
Optical laser stylus, 141
Optimization, 274
Out-of-roundness, 106

Paper surfaces, 141
Phase meters, 173
Physical model, 266
Polymers, 221
Positioning accuracy, 180
Positioning, 180
Precise positioning, 39
Probe calibration, 150
Profile, 166
Profilometers, 141

Relocation, 77
Repetitive bracketing method, 93
Resonating, 248
Roller bearing, 166
Rotating disk electrode, 6

Scanning electron microscope, 112
Sensor, 266
Shape measurement, 86
Silicon carbide, 115
Single-point diamond machining, 221
Software, 121
Straightness, 158, 274
Subnanometric accuracy, 281
Surface finish, 100
Surface roughness, 141
Surface topography, 77

Tool steel, 100
Tool vibrations, 258
Transducer, 248
Twist-roller friction drive, 180

Ultraprecision cutting machine, 86
Ultraprecision positioning, 180
Uncertainty, 150

Waviness, 166

Zone-plate interferometer, 86